



Product Data Sheet

AmberLite™ 62i Inert Resin

Polyethylene, Inert Resin for Industrial Demineralization Applications

Description

AmberLite™ 62i Inert Resin is a floating, non-functionalized, transparent, amorphous-shaped resin with properties specifically designed for use as an upper layer in up-flow regenerated ion exchange systems, such as UPCORE™ Packed Bed Systems. This inert resin has a specific gravity lower than water, which ensures it will stay above the ion exchange resin bed. Its self-distributing properties allow it to evenly cover the available cross-sectional area, forming a protective layer that allows dirt and resin fragments to pass through while retaining the resin bed during the compaction/bed-lift step prior to regeneration.

Applications

- Demineralization
- Industrial softening
- Condensate polishing

System Designs

- Packed beds
 - for UPCORE™ Packed Bed Systems or other up-flow regenerated packed beds
 - configured as a layered bed
- Counter-current / Air hold-down

Historical Reference

AmberLite™ 62i Inert Resin has previously been sold as DOWEX UPCORE™ IF-62 Inert Resin.

Typical Properties

Physical Properties	
Polymer	Polyethylene
Type	Inert
Functional Group	None
Physical Form	White pellets
Particle Size	
Particle Diameter	2.5 – 4.0 mm
Density	
Particle Density	0.95 g/mL
Shipping Weight	620 g/L
Temperature Range	5 – 110°C (41 – 230°F)
pH Range	0 – 14



Suggested Operating Conditions

For additional information regarding recommended minimum bed depth, operating conditions, and regeneration conditions for [separate beds](#) (Form No. 45-D01131-en) in water treatment, please refer to our Tech Fact.



Hydraulic Characteristics

Estimated pressure drop for AmberLite™ 62i Inert Resin as a function of service flowrate and temperature is shown in Figure 1a and a magnified scale of the same is shown in Figure 1b. These estimated pressure drop expectations are valid at the start of the service run with clean water and a well-classified bed.



Product Stewardship

DuPont has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our product stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our product stewardship program rests with each and every individual involved with DuPont products—from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.

Customer Notice

DuPont strongly encourages its customers to review both their manufacturing processes and their applications of DuPont products from the standpoint of human health and environmental quality to ensure that DuPont products are not used in ways for which they are not intended or tested. DuPont personnel are available to answer your questions and to provide reasonable technical support. DuPont product literature, including safety data sheets, should be consulted prior to use of DuPont products. Current safety data sheets are available from DuPont.

Please be aware of the following:

- **WARNING:** Oxidizing agents such as nitric acid attack organic ion exchange resins under certain conditions. This could lead to anything from slight resin degradation to a violent exothermic reaction (explosion). Before using strong oxidizing agents, consult sources knowledgeable in handling such materials.

Have a question? Contact us at:

www.dupont.com/water/contact-us

All information set forth herein is for informational purposes only. This information is general information and may differ from that based on actual conditions. Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries. Please note that physical properties may vary depending on certain conditions and while operating conditions stated in this document are intended to lengthen product lifespan and/or improve product performance, it will ultimately depend on actual circumstances and is in no event a guarantee of achieving any specific results. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. No freedom from infringement of any patent or trademark owned by DuPont or others is to be inferred.

©2019 DuPont. DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or © are owned by affiliates of DuPont de Nemours Inc., unless otherwise noted.

DOWEX UPCORE™ and UPCORE™ are trademarks of The Dow Chemical Company used under license by DuPont.

